



- Nail Paraseal LG every 8" (20cm) O.C.
- Paraseal LG (bentonite side facing installer) (See detail #'s 10841 and 10845)
- Compacted earth or granular base min. 85 proctor
- 4" (10 cm)
- Paragrangular Cant
- 2" x 2" (50mm x 50mm)
- Superstop, install 2" from outer wall
- 6" x 6" (15cm x 15cm) Paraseal LG corner strip bentonite against concrete. Staple edges every 3" (8cm) O.C.
- Paraseal LG, bentonite against concrete placed to the interior of footing formwork

**Note: Paraseal products require a minimum 24 psf compaction/ confinement to be effective.**

This detail is intended for conceptual purposes only. Detail must be reviewed by a project/design professional. See [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date product information.

Rev	Date	Description	By
1	10/10/2013	Update Detail	KAB



www.tremcosealants.com  
 3735 Green Road \* Beachwood, OH 44122  
 Phone : 866-209-2404 \* Fax: 216-766-5535

Project: Below Slab-on-Grade  
 Detail: Tie-In Between Blindside Wall/Footing and Floor

Drawn by: KAB Checked by: WH Scale: None

Sheet Number:  
 Date: 8/26/2009

File Name:  
 10857

Rev #  
 1