

PARASEAL LG, BENTONITE SIDE FACING INSTALLER

FILL CUT RAKER BLOCKOUT VOID WITH CEMENT OR GROUT

PARASEAL LG TARGET SHEET TO BE SECURED WITH NAILS AND WASHERS AT THE CORNERS AND WITH BOX CROWN STAPLES EVERY 3" O.C. THEREAFTER

PARASTICK N DRY OR SUPERSTOP WRAPPED AROUND PIPE AND SECURED WITH TIE-WIRE

DETAIL RAKER PIPE PRIOR TO SHOTCRETE WALL; A BLOCKOUT VOID WILL BE CREATED IN ORDER TO CUT THE RAKER PIPE AFTER PLACEMENT OF WALL

PARAMASTIC OR DYMONIC 100

TREMDRAIN, AS SPECIFIED

FILL CUT RAKER PIPE WITH CEMENT OR GROUT

NOTES: PARASEAL PRODUCTS REQUIRE A MIN 24 PSF OF COMPACTION/CONFINEMENT IN ORDER TO FUNCTION AS DESIGNED.

NOT RECOMMENDED FOR USE IN SUBMERGED CONDITIONS.

The architecture, engineering, and design of the project using the Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Tremco to ensure you have the most recent version.

Paraseal LG Blind Side Walls



Detail: Paraseal LG at Raker or Waler

File Name:

BSW-LG-P-04

Drawn by: KAB

Checked by: SP/WH

Scale: NTS

Date: 3/4/2022



Construction Products Group

Tremco Technical Support: 866-209-2404

www.tremcocpg.com