


NOTE:
 PARASEAL PRODUCTS REQUIRE A MIN 24 PSF OF
 COMPACTION/CONFINEMENT IN ORDER TO FUNCTION AS DESIGNED
 NOT RECOMMENDED FOR USE IN SUBMERGED CONDITIONS



- POLYETHYLENE SHEET 6 MIL MIN
- PERMANENT SEAM TAPE CENTERED OVER SEAM
- LAP SEAMS 4" MIN. AND SECURE WITH PINS AND WASHER OR WIDE CROWN BOX STAPLES LOCATED ONLY IN THE SEAM AREA AT 8" O.C. SEAMS AND FASTENER HEADS ARE TO BE COVERED WITH PERMANENT SEAM TAPE.
- PARASEAL LG; HDPE SIDE FACING UP
- MAT SLAB
- COMPACTED GRANULAR BASE OR SOIL, COMPACTED TO 85% MIN. MODIFIED PROCTOR

The architecture, engineering, and design of the project using the Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Tremco to ensure you have the most recent version.

Paraseal LG Below Slab on Grade - HDPE Side Up



Detail: Paraseal LG Below Slab on Grade Seam - Option 2 Section				File Name:
Drawn by: HDE	Checked by: WH	Scale: NTS	Date: 5/16/2022	PE-BSOG-LG-S-04
www.tremcocpg.com				

