

EXTERIOR FINISH AS SPECIFIED

HORIZ/VERT REINFORCEMENT
AS PER CODE OR AS SPECIFIED

WET SET DOWELS TO MATCH
VERTICAL REINFORCEMENT BETWEEN
POUR OR AS SPECIFIED

ENVIRO-DRI

FINISH GRADE
MINIMUM 6" (152mm)
OR AS PER CODE

2-3" MIN.

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE COAT
OR OTHER APPROVED EPS
COMPATIBLE FINISH

TREMPRO 160

DRAINAGE, AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM BOARD

BLOCKING BETWEEN JOISTS

JOISTS/TRUSSES AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM BOARD

PROPRIETARY EMBEDDED JOIST
ANCHORAGE SYSTEM OR EQUIVALENT

NUDURA STANDARD FORM UNIT

$\frac{1}{2}$ " (13mm) GYPSUM BOARD

NOTE: SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE RESPONSIBILITY OF THE DESIGNER