

Enviro-Dri® Window & Door

Cold-applied, self-adhering membrane

DATA SHEET

Product Description

Enviro-Dri Window & Door is a cold-applied self-adhering membrane composed of butyl rubber with a Kraft paper liner for easy installation. This product fully integrates with the Enviro-Dri Weather-Resistant Barrier System to provide you with the next level of protection against air and moisture intrusion around window, door and some utility penetrations.

Basic Uses

Enviro-Dri Window & Door is used to seal around window and door assemblies, as well as some utility penetrations.

Features & Benefits

- 4" or 6" wide x 75' long roll
- Butyl-based material offering exceptional adhesion to most building materials
- Specifically engineered and designed to provide an air and moisture seal around doors and windows. Integrated seamlessly with the Enviro-Dri Field Membrane
- Resists UV degradation for up to 1 year of direct sun exposure
- Provides strong and immediate adhesion over a wide range of installation temperatures, and remains pliable at low temperatures
- Imprinted with the Enviro-Dri brand to extend the brand recognition for your protected homes

Please refer to our website at <u>www.tremcosealants.com</u> for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL MEMBRANE PROPERTIES						
PROPERTY		DESCRIPTION				
COLOR		Black				
THICKNESS		20 mils (16 mils adhesive; 4 mils backing)				
APPLICATION TEMPERATUR	E RANGE	30°F - 150°F				
PACKAGING		Roll Width: 4" (12 rolls / carton) 6" (8 rolls / carton)	Roll Length: 75'			
STORAGE		Store in unopened container at between 40° - 90°F				
PROPERTY	TEST METHOD	TYPICAL RESULTS				
TENSILE STRENGTH	ASTM D 1000	60 lb/in				

0420/EDWDDS

Please refer to our website at www.tremcosealants.com for the most up-to-date Data Sheet.

Tremco	Construct	tion Proc	lucts	Group
				O. O.P

3735 Green Rd Beachwood OH 44122 800.876.5624