


**Product Description**

Tremco Poly-Wej Gaskets are designed for use in compression glazing systems. They are available as a standard in EPDM. When used in combination with Tremco POLYshim™ II Tape and gunnable sealants, the Poly-Wej Glazing System is formed. This system is proven and "clean and easy" to install, affording many years of excellent performance.

**Metal Requirements**

Tremco Poly-Wej Gaskets require a .062" x .062" (1.57 mm x 1.57 mm) metal nub for proper engagement. Custom Poly-Wej gaskets can be designed or may be available to accommodate specific metal nub configurations not shown.



-  PS-1125E for 1/8" (3.18mm) F.C.  
PS-1125N
-  PS-1126E for 3/16" (4.78mm) F.C.  
PS-1126N
-  PS-1127E for 1/4" (6.35mm) F.C.  
PS-1127N

\*F.C.= Face Clearance

**Availability**

Tremco Poly-Wej Gaskets for 1/8"(3.18 mm), 3/16" (4.78 mm) and 1/4" (6.35 mm) designed face clearances are immediately available from the Tremco plant located in Ashland, Ohio. Their costs can be obtained from your local Tremco Representative or our Customer Service Department in Ashland, Ohio at: 800- 321-6357.

Poly-Wej gasket for 3/8"( 9.52 mm) designed face clearance is available as a custom order with a 3 to 5 week lead time.

**Packaging**

Tremco Poly-Wej Gaskets are packaged based on customer requirements, profile size, configuration and the need for molded picture frame gaskets.

**Warranty**


Tremco warrants its Products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Products proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

## TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	EPDM	NEOPRENE*
Shore "A" Hardness	ASTM D2240	68 - 71	68 - 72
Compression Set, 22 hr @ 212 °F (100 °C)	ASTM D395	24 - 28%	22 - 26%
Ozone Resistance, 100 mPa 100 hr @ 104 °F (40 °C) 20% Elongation	ASTM D1149	No Cracks	No Cracks
Tensile Strength	ASTM D412	1810 - 1925 psi (12.5 - 13.3 MPa)	1850 - 2050 psi (12.8 - 14.1 MPa)
Elongation @ Rupture	ASTM D412	350 - 530%	235 - 350%
Tear Strength	ASTM D624	143 - 209 lb/in (25 - 36.6 kN/M)	163 - 190 lb/in (28.5 - 33.3 kN/M)
Brittleness Temperature @ -40°F (-40°C)	ASTM D746	Pass	Pass
Flame Propagation, Option II	ASTM C1166	No Limit	No Limit



0316/PWGSKTSDS-GL

### Tremco Commercial Sealants & Waterproofing

3735 Green Rd  
Beachwood OH 44122  
216.292.5000 / 800.321.7906

1451 Jacobson Ave  
Ashland OH 44805  
419.289.2050 / 800.321.6357

220 Wicksteed Ave  
Toronto ON M4H1G7  
416.421.3300 / 800.363.3213

1445 Rue de Coulomb  
Boucherville QC J4B 7L8  
514.521.9555

