



TECHNICAL DATA SHEET

TREMSTOP® ACRYLIC

Gunnable, Acrylic Latex
Firestop Sealant

PRODUCT DESCRIPTION

TREMstop® Acrylic is a gunnable, acrylic latex sealant designed for use in firestopping applications, including both joints and through-penetrations.

BASIC USES

TREMstop Acrylic is intended for use in fire-rated concrete, wood, floor/ceiling, and gypsum assemblies, including the following:

- Metal, plastic, or insulated pipes
- Cables and cable trays
- Ducts
- Static joints
- Dynamic joints
- Acoustically rated assemblies

FEATURES & BENEFITS

TREMstop Acrylic is an easy to apply, all-purpose sealant that accepts paint once fully cured. It features excellent movement and superb unprimed adhesion to a wide range of substrates. When installed in accordance with a tested firestop system, TREMstop Acrylic affords code compliance for both through-penetrations and fire-rated joints.

TREMstop Acrylic meets or exceeds the requirements of the following specifications:

- UL 1479 (ASTM E814)
- UL 263 (ASTM E119)
- UL 723 (ASTM E84)
- UL 2079 (ASTM E1966)
- ASTM E1399
- ASTM E90
- CAN/ULC-S115
- CAN/ULC-S101M

The Greenguard Gold certification on TREMstop Acrylic ensures safety for use in the most sensitive indoor environments including hospitals and schools.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, 20 oz (600 mL) sausages, 28.7 oz (850 mL) quart cartridges, and 5 gal (19 L) pails.

COLORS

Available in Rust Red, Limestone, and White. Custom colors are available upon request. Contact Tremco Customer Service for more information.

LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco. Refer to UL listings at www.UL.com. Contact Tremco Technical Services for additional information.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Flame Spread	ASTM E84	15
Smoke Development	ASTM E84	0
Movement Capability	ASTM C719, UL2079; Class I, II, III	± 33%
Peel Strength	ASTM C794	15 to 25 (<i>substrate dependent</i>)
VOC Content		35 g/L

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSA-DS/0123



Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com