TECHNICAL DATA SHEET

TREMSTOP® ACRYLIC SP

Sprayable, Acrylic Latex Firestop Sealant

PRODUCT DESCRIPTION

TREMstop® Acrylic SP is a sprayable, acrylic latex sealant designed for use in firestopping applications, including both joints and through-penetrations. TREMstop® Acrylic SP can also be used in smoke-rated partitions or joints and to prevent sound transmission through unprotected openings.

BASIC USES

TREMstop Acrylic SP is for use on metal pipe (Canada only), static joints, and dynamic joints in fire-rated concrete, wood, floor/ceiling, gypsum wall assemblies and perimeter fire barrier joints. Additionally, TREMstop Acrylic SP can be used for through penetrations and joints in smoke- and/or sound-rated partitions and to restore the STC of sound-rated assemblies.

FEATURES & BENEFITS

TREMstop Acrylic SP is an easy to apply, multipurpose sealant that accepts paint once fully cured. The spray application method provides significant labor savings over a gun-grade sealant, particularly on long joint runs.

TREMstop Acrylic SP features excellent movement and superb unprimed adhesion to a wide range of substrates. When installed in accordance with a tested firestop system, TREMstop Acrylic SP affords code compliance for both through-penetrations and fire-rated joints. It also provides a fast and easy solution for restoring the STC rating of a sound-rated assembly.

TREMstop Acrylic SP meets or exceeds the requirements of the following specifications:

- UL 1479 (ASTM E814)
- UL 263 (ASTM E119)
- UL 723 (ASTM E84)
- UL 2079 (ASTM E1966)
- ASTM E1399
- ASTM E90
- ASTM 2307
- CAN/ULC-S115
- CAN/ULC-S101M

The Greenguard Gold certification on TREMstop Acrylic SP ensures safety for use in the most sensitive indoor environments including hospitals and schools.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 5 gal (19 L) pails.

COLORS

Available in Rust Red, Limestone, and White. Contact Tremco Customer Service for more information.

LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco. Refer to UL listings at www.UL.com. Contact Tremco Technical Services for additional information.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit https://www.tremcosealants.com/warranties/ for details.

TYPICAL PHYSICAL PROPERTIES		
PROPERTY	**TEST METHOD**	**TYPICAL RESULTS**
Flame Spread	ASTM E84	60
Smoke Development	ASTM E84	120
Movement Capability	ASTM C719, UL2079; Class I, II, III	± 25%
STC Rating	ASTM E90	67
OITC Rating	ASTM E90	55
Peel Strength	ASTM C794	10 to 20 (substrate dependent)
VOC Content		40 g/L
Antifungal		Contains an antifungal additive

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSASP-DS/0826