



TECHNICAL DATA SHEET

DRAINSTAR® WALL DRAIN

Prefabricated Soil Sheet for Below Grade Waterproofing

PRODUCT DESCRIPTION

DrainStar Wall drain is a two-part prefabricated soil sheet drain designed to control below grade water. The fabric allows water to pass into the drain core, while restricting soil particles from entering. The core allows water to gravity drain to the installed DrainStar StripDrain or drain tile and gravel system, and then to the designated drainage exits, such as daylight, a sump crock, or weep hole exits.

PACKAGING

Wall Drain 90

- 4' x 50' rolls
- 6 rolls per pallet

Wall Drain 720

- 6' x 65.5' rolls
- 6 rolls per pallet

Wall Drain 960

- 8' x 65.6' rolls
- 6 rolls per pallet

ATTACHMENT METHOD

DrainStar Wall Drain can be attached using powder actuated fasteners, gas cartridge nails, or hand installed using masonry nails. Nails of ½", ¾" or 1" length are acceptable, used with washers.

COLLECTION SYSTEMS

DrainStar Wall Drain is used as a drainage and protection layer with Tremco waterproofing and damp proofing membranes.

INSTALLATION INSTRUCTIONS

Installation Instructions for Foundation Walls

- A. Cut DrainStar Wall Drain from bottom edge to desired height, ensuring that the bottom edge of the Wall Drain will rest directly above the weep holes, and the top flanged edge will terminate at desired finished grade.
- B. When using a second roll on top of the roll that sits on the footing, the top roll fabric flange must shingle over the first roll a minimum of one inch. The shingled overlap area should be fastened.
- C. Ensure all roll ends and edges are covered with fabric by overlapping a new roll of DrainStar Wall Drain three inches over the end of the existing roll and covering any exposed core on either roll. At terminations, remove two to three inches of the core and tuck excess fabric behind the core and fasten.
- D. All exposed core should be covered with fabric.

Retaining Wall Applications

- A. For retaining wall applications with mid-wall weep hole exits, the DrainStar Wall Drain does not need to extend to footing level. The DrainStar Wall Drain bottom edge will rest directly above the weepholes.

B. Follow Installation Instructions for Foundation Walls for all other steps.

HANDLING REQUIREMENTS

Installation

- Limit unpackaged material UV exposure to a cumulative maximum of 14 days during installation.
- Do not install materials during high wind events.
- Do not install materials when ambient temperatures are below 20°F or above 100°F.
- Do not expose materials to chemicals that are strong acids, strong bases, or high in solvents content.
- Protect materials from site construction damage, flames, and other environmental conditions that may damage the materials.

Storage

- Store materials in protected environment until time of installation.
- Materials not shipped in UV-resistant bags must be stored indoors or under separate UV-protective cover to protect materials from exposure to direct sunlight.
- UV-resistant bagged materials may be stored in outdoor UV-exposed environments for a cumulative maximum of 180 days.

TYPICAL PHYSICAL PROPERTIES

	TEST METHOD	WALL DRAIN 90	WALL DRAIN 720	WALL DRAIN 960
FABRIC				
Material		Polypropylene	Polypropylene	Polypropylene
Grab Tensile Strength	D-4632	90lbs	115lbs	115lbs
Grab Elongation	D-4632	65%	70%	70%
CBR Puncture Strength	D-6241	225lbs	320lbs	320lbs
Puncture Resistance	D-4833			
Water Flow Rate	D-4491	190gpm/ft2	150gpm/ft2	150gpm/ft2
Permittivity	D-4491	2.7sec -1	2.2sec -1	2.2sec -1
Apparent OpeningSize	D-4751	50sieve	70sieve	70sieve
UV Resistance	D-4355	70%/500	70%/500	70%/500
CORE				
Material		Polystyrene	Polystyrene	Polystyrene
Thickness	D-5199	.25in	.315in	.315in
Compressive Strength	D-1621	9,000psf	5,200psf	5,200psf
FlowRate*	D-4716	12.5gpm/ft	12.5gpm/ft	12.5gpm/ft

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

DSWD-DS/0624

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com