



TECHNICAL DATA SHEET

TREMprime™ BE Primer

SBS polymer-based primer

PRODUCT DESCRIPTION

TREMprime® BE is a VOC-compliant, high-performance adhesive primer designed to promote adhesion across a wide range of building enclosure substrates. Formulated for use with ExoAir® air barrier membranes and TREMproof® waterproofing membranes, it provides reliable compatibility across full-assembly installations.

BASIC USES

TREMprime BE is designed for use with TREMproof™ 560A, self-adhesive waterproofing membranes and ExoAir membranes.

Ideal for use on:

- Concrete substrates
- Wood surfaces
- Gypsum board panels
- Porous and non-porous substrates

APPLICATION

The substrate must be clean, dry, and free of dust, grease, or other contaminants.

TREMprime BE may be applied with a brush, roller, or sprayer on metal, concrete, wood, gypsum sheathing, and other approved substrates.

Coverage varies by porosity and texture; average coverage is 0.7 to 1 gal/100 ft² (0.3 to 0.4 L/m²).

Spraying equipment recommendations:

- Spray tip size: 20 to 25 mils
- Pressure: 1300 psi continuous

Apply a light, uniform coat.

Allow the primer to develop a tack, non-transferable film (typically 15 to 30 min) prior to installing any membrane. Prime only those surfaces that will be completed that day. If fully dry, reprime to ensure successful adhesion.

Condition the material so it meets the minimum recommended temperature.

- Minimum application temperature: 25 °F (–4 °C).
- The product must be at minimum 50 °F (10 °C) at the time of application.

Uncured primer can be cleaned with water. Cured material may require solvents such as mineral spirits, varsol, or xylene. Keep out of reach of children. Harmful if inhaled, swallowed or when in contact with the skin. Do not dispose of residues in drains.

AVAILABILITY

Available immediately through your local Tremco or Nudura Sales Representative, Tremco distributors, or warehouse.

To locate a distributor near you, visit: <https://www.tremcosealants.com/>

PACKAGING

Available in 1-gal (3.8-L) and 5 Gal (19.8L) pails.

Can be stored up to 24 months in original unopened container.

LIMITATIONS

- Minimum application temperature 25 °F (-4 °C).
- Keep from freezing.
- Not recommended for plastic surfaces, metal surfaces or water-repellent treated panels.
- Do not use to seal self-adhesive membrane joints, as a primer between two membranes or on asphaltic boards.
- Do not apply heavy or thick coats of primer.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Specific Gravity at 68 °F (20 °C)		.79 kg/L
Color		Copper
Solids by Weight		24%
Brookfield Viscosity, 77 °F (25 °C)		200 cP
Drying Time		Between 15 minutes to 60 minutes, depending on temperature and quantity applied.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TPBE-DS/0226

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com