



TECHNICAL DATA SHEET

TREMPRIME™ SILICONE METAL PRIMER

Single Component Silicone Primer
for Metal Substrates

PRODUCT DESCRIPTION

TREMPRIME™ Silicone Metal Primer is a one component primer used to enhance adhesion of Tremco Silicone Sealants to a variety of building materials which includes metals, wood, and masonry.

FEATURES & BENEFITS

- Enhances the adhesion of Tremco silicone sealants to a variety of building materials
- Fast drying
- Easy application

AVAILABILITY

Readily available in 16 oz. bottles from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

COLORS

Available in Clear.

STORAGE

Store in dry conditions below 75 °F (25 °C). Changes in appearance from its original clear solution may indicate contamination or loss of shelf life.

SHELF LIFE

1 year if stored as recommended in original, unopened containers.

SURFACE PREPARATION

- Surfaces to be primed shall be clean, dry, and free of dust and other contaminants.
- Metal surfaces should first be cleaned with Methyl Ethyl Ketone (MEK) or solvents as recommended by Tremco to remove oil, grease, dirt, and other contaminants, then wiped dry with clean rags.

APPLICATION

- TREMPRIME Silicone Metal Primer should be used as furnished.
- Apply a uniform continuous file of primer.
- Avoid excess of primer to best results.
- Allow primer to air dry prior to applying sealant over application.
- Prime only as much surface as can be sealed the same day.
- Primer should be applied from a clean container, filled from the original bottle, and original bottle kept closed.
- Properly discard any unused primer.

CLEANING

Spills should be cleaned off immediately before TREMprime Silicone Metal Primer dries.

LIMITATIONS

TREMprime Silicone Metal Primer must be completely dry before applying the silicone sealant. Additionally, if the sealant has not been applied after 8 hours, the surface must be cleaned with IPA and reprimed with TREMprime Silicone Metal Primer.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TPSMPDS/0425

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com